




SSI Shredding Systems



PRI-MAX®



DUAL-SHEAR®



QUAD®



UNI-SHEAR®

TECHNOLOGY OVERVIEW



PRI-MAX®

PRIMARY REDUCERS

SSI's PRI-MAX® two-shaft primary reducers are commonly employed in volume reduction or pre-shredding applications with a wide range of commingled materials, including unsorted waste. Ideal for primary liberation of materials, PRI-MAX® machines output larger, recognizable items well-suited for feeding a sort line or other recovery process so that “non-shreddables” or marketable commodities can be removed prior to further processing. PRI-MAX® can also be configured as a bale-breaker or bag breaker.

PERFORMANCE: 10 to 150 tons per hour depending on materials and PRI-MAX® model.

OUTPUT: “Chunks” that are sized between 6” and 24” nominal based on cutting table configuration.



DUAL-SHEAR®

TWO-SHAFT SHREDDERS

SSI's Dual-Shear® line of two-shaft shredders are commonly employed in volume reduction, product destruction or primary shredding applications. These low-speed, high-torque industrial shredders are ideal for processing compressible materials such as rubber, metals and many plastics that need to be “cut” in order to be sized reduced. Dual-Shear® shredders are very versatile machines that can be configured to process a wide range of materials.

PERFORMANCE: 0.5 to 70 tons per hour depending on materials and Dual-Shear® model.

OUTPUT: “Strips” roughly the width of the cutters that vary in length.





QUAD®

FOUR-SHAFT SHREDDERS

SSI's Quad® four-shaft shredders process a wide range of material streams to a consistently small size in a single pass. Quads employ proven low-speed technology and an integrated sizing screen to generate uniform, well-liberated output, without incurring damage from metals and other hard objects. By removing the screen, Quads can also be operated like a two-shaft shredder. They are ideal for commingled materials without overly thick metals, and their large “throat” opening allows even large, bulky items to be processed.

PERFORMANCE: 0.5 to 20 tons per hour depending on materials Quad® model and screen size.

OUTPUT: “Chips” that are roughly the same size as the holes in the integrated screen. Typically 3/4” to 8”. Consistent sizing.




UNI-SHEAR®

ONE-SHAFT SHREDDERS & GRINDERS

SSI's Uni-Shear® one-shaft shredders are ideal for size reduction of consistent materials such as paper, plastic, foil, foam, textiles, aluminium, tire chips and more. These shredders can work as stand-alone machines in some applications, or as secondary machines that further reduce the output from primary shredders after metals have been removed. Small footprint and low parts costs make Uni-Shears® an efficient option for small particle size.

PERFORMANCE: 0.5 to 15 tons per hour depending on materials, Uni-Shear® model, use and screen size.

OUTPUT: “Chips” that are roughly the same size as the holes in the integrated screen. Typically 1/2” to 3”. Consistent sizing.





WHAT **NEEDS** SHREDDING?®



SSI Shredding Systems, Inc.

Tel: +1 (503) 682-3633 | www.ssiworld.com | sales@ssiworld.com

© Copyright 2017 SSI Shredding Systems, Inc. All rights reserved.
Illustrations, specifications and descriptions presented reflect standard product
at time of publication and are subject to change without notice. Dimensions
are approximate. Photographs may include optional equipment and accessories.